











		<b>Videosec EXPORT PRICE LIST (US\$)</b>		<a href="http://www.videosec.com">www.videosec.com</a>		<b>US\$</b>	
6724 Szeged, Ustokos u. 12/b, Hungary. Tel: +36 62 458 585, Fax: +36 62 458 586, E-mail: eurotech.kft@gmail.com							
		<b>Description</b>		<b>Ver: June-23-2011</b>		<b>Model</b>	
<h2 style="text-align: center;">On Sale July-2011</h2>							
	<p><b>D&amp;N Box IP Camera - ICR (IR Cut filter change mechanism) - PoE</b>          1.3M progressive sensor, Max. 1280*1024 Stream,  <b>H.264/MPEG4/MJPEG</b> Tri-CODEC, Including fixed lens  <b>DC iris</b> - CS mount, 2-way audio, DI/DO, RS485, Power: 12VDC or PoE          SDK: AXIS like API/CGI (Open API for software integration)  <b>Recommended with: Megapix. CS, HD Lens, f=2.4-6mm</b>          Horizontal angle of view: 85°-33°  <b>Attention: for HD cameras can be used only HD (megapixel) lens</b>          Delivery (included) with: <b>NUUO IP-P LITE</b> Licence</p>	<p><b>ICR mechanism Built In</b>  <b>DC Auto Iris function Built In</b>  <b>CS Mount Lens Not Included</b>          Optional CS Lenses:          Manual VF. Lens, f=2.2-6mm          Manual VF. Lens, f=2.8-8mm          DC Iris VF. Lens, f=2.8-8mm          CS - 1.55mm = 130°          CS - 3.6mm = 58°          CS - 6mm = 33°          CS - 12mm = 17°</p>	<p style="text-align: center;"><b>IBF-211</b></p>	<p style="text-align: center;">129.00</p>			
	<p><b>Megapixel IR Corrected Lens • IR Corrected</b>  <b>Megapixel CS MOUNT - 1/3" Manual Iris</b>          Varifocal Lens, f=2.4-6mm / F1.6-Close          1/3"- Horizontal angle of view: 110°-46°          1/4"- Horizontal angle of view: 85°-33°          High Resolution Lens for Megapixel Cameras 1.3-2 Mpix.  <b>Megapixel</b></p>	<p><b>CS MOUNT LENS NOT INCLUDED</b>  <b>Recommended: HD Lens: MLVC-2460 f=2.4-6mm</b></p>	<p style="text-align: center;"><b>MLVC-2460</b></p>	<p style="text-align: center;">44.10</p>			
 	<p><b>Indoor IP 3-Axis Dome Camera - PoE</b>          1.3M progressive sensor, Max. 1280*1024 Stream,  <b>H.264/MPEG4/MJPEG</b> Tri-CODEC, 2-way audio,          3 axis cradle, Fixed lens, 12VDC / PoE          SDK: AXIS like API/CGI (Open API for software integration)          Delivery (included) with: <b>NUUO IP-P LITE</b> Licence</p>	<p><b>HD Lens: 2.8mm/F2.0</b>  <b>Horizontal Angle of View: 78°</b>          Optional Lenses:          2.1mm = 100°          3.6mm = 58°          6mm = 33°          8mm = 25°          12mm = 17°          16mm = 12°</p>	<p style="text-align: center;"><b>ID-209</b></p>	<p style="text-align: center;">79.00</p>			
 	<p><b>Vandal IP 3-Axis dome Camera- VF lens - PoE</b>          1.3M progressive sensor, 4-9mm lens,          Max. 1280*1024 Stream, <b>H.264/MPEG4/MJPEG</b> Tri-CODEC,          2-way audio, IP66 Vandal housing, 12VDC / PoE          SDK: AXIS like API/CGI (Open API for software integration)          1.75 Kg          Delivery (included) with: <b>NUUO IP-P LITE</b> Licence</p>	<p><b>Varifocal Lens 4-9mm/F1.7</b></p>	<p style="text-align: center;"><b>IDA-211</b></p>	<p style="text-align: center;">147.20</p>			
 	<p><b>Vandal IR IP 3-Axis dome Camera- VF lens - PoE</b>          1.3M progressive sensor, 2.7-9mm VF AI lens, 24pcs LED for D&amp;N          Max. 1280*1024 Stream, <b>H.264/MPEG4/MJPEG</b> Tri-CODEC,          2-way audio, IP66 Vandal housing, 12VDC / PoE          SDK: AXIS like API/CGI (Open API for software integration)          1.75Kg          Delivery (included) with: <b>NUUO IP-P LITE</b> Licence</p>	<p><b>DC Autoiris Varifocal Lens with Changeable IR Cut Filter 2.7-9mm/F1.6</b>  <b>Horizontal Angle of View: 83°-22°</b></p>	<p style="text-align: center;"><b>IDA-210</b></p>	<p style="text-align: center;">199.00</p>			
 	<p><b>1ch Video Server with PoE &amp; SD Card</b>  <b>H.264/MPEG4/MJPEG</b> Tri-CODEC, Max. 704*480@30fps,          2-way audio, DI/DO, RS485, SD card interface.  <ul style="list-style-type: none"> <li>• Power IN: 12VDC / PoE</li> <li>• Power OUT: 12VDC-1A for CCTV Camera</li> <li>• Delivery (included) with: <b>NUUO IP-P LITE</b> Licence</li> <li>• fully integrated to NUUO PC Based and Standalone NVRs (easy to connect by "auto-detect" function)              SD card is not included</li> </ul> </p>	 	<p style="text-align: center;"><b>IS-240</b></p>	<p style="text-align: center;">84.08</p>			