

Accessories for CCTV



AH-375
Outdoor camera housing IP65



CB-210
Bracket for AH-375



H-230
Heater for AH-375



ML-350
L Bracket for AH-375



PB-115
Plastic Bracket



DB-100
Dome Bracket



ADB-150
Armour Dome Bracket



WB-D
IR Dome Wall-bracket



IB-D
IR Dome Pendant Bracket



OSD-C
IR Dome OSD Controller



RSC-485
universal RS-485 Controller



LCD-8P
8" LCD CCTV Hi-Res. Color Monitor



AM-02
Audio Module 12VDC-20mA Out: RCA 2Vp-p



BNC-P
BNC+BNC Patch Cord Cable Ø3mm/75Ω black color, available length: 1.5m - 3m - 5m - 10m - 20m

CCTV Lenses

METAL



YV2.6x3C-SA2-L
FUJINON 1/3" CS-mount Lens
f=3.0~8mm/F1.4~ Close
Aspherical - **Auto Iris DC**
HVOF: 1/3"=95°~34°



YV2.8x2.8LA-SA2-L
FUJINON 1/3" CS-mount Lens
f=2.8~8mm/F0.95~ Close
Aspherical - **Auto Iris DC**
HVOF: 1/3"=99°~34°



YV2.8x2.8LA-2
FUJINON 1/3" CS-mount Lens
f=2.8~8mm/F0.95~ Close
Aspherical - **Manual Iris**
HVOF: 1/3"=99°~34°



LVC-0660D
Varifocal - DC Iris
f=6~60mm/F1.6
Horizontal: 45°~3°



LVC-0615D
Varifocal - DC Iris
f=6~15mm/F1.4
Horizontal: 45°~18°



LVC-3580D
Varifocal - DC Iris
f=3.5~8mm/F1.2
Horizontal: 75°~35°



LVC-0615M
Varifocal - M. Iris
f=6~15mm/F1.4
Horizontal: 45°~19°



LVC-3580M
Varifocal - M. Iris
f=3.5~8mm/F1.4
Horizontal: 75°~35°



LC-04
f=4mm/F1.6
Horizontal: 70°



LB-178
Fixed Iris f=1.78mm/F3.0
Horizontal: 145°



LB-025
Fixed Iris f=2.5mm/F2.0
Horizontal: 113°



LB-297
Fixed Iris f=2.97mm/F2.0
Horizontal: 92°



LB-036
f=3.6mm
Horizontal: 78°



LVB-2810
Board Lens
2.8~10mm/F1.6
HVOF: 1/3"=99°~27°



LB-06
Fixed Iris f=6mm/F2.0
Horizontal: 45°



LB-08
Fixed Iris f=8mm/F2.0
Horizontal: 35°



LB-12
Fixed Iris f=12mm/F2.0
Horizontal: 25°



LB-16
Fixed Iris f=16mm/F2.0
Horizontal: 17°



LP-037
Pin-Hole f=3.7mm/F2.0
Horizontal: 74°



LC-06
f=6mm/F1.6
Horizontal: 45°



LC-08
f=8mm/F1.6
Horizontal: 34°



LC-16
f=16mm/F1.6
Horizontal: 17°

Board (M12x0.5) CCTV Camera Lenses - format 1/3"

Housings & Brackets

520ml



AH-375

Outdoor **Camera Housing**

All parts made of Aluminium

Outlook Dimension:

138x117(H)x375(L)mm -1.35Kg



ML-350

Metal Ceiling "L" **Bracket** for AH-375

Size: 350(High)X280(Wide)mm

Max. Load 10Kg.

Beige Color, Weight: 1.16 Kg.



CB-210

Metal Cable management

Bracket for AH-375

214X120X80mm - 0.55Kg,

Max. Load 10Kg.



PB-115

Plastic Camera Bracket

Color: Beige or Black

Size: Ø80 x 115(H)mm - 120g

Max. Load: 1.2Kg



RSC 485 Joystick Keyboard RS-485 Controller



- PELCO-D, PELCO-P, ALEC, SAMSUNG, VIDEO-BO1
- HD600, TOTA, KALATEL, VCLDOME, REDAPPLE
- SANTACHI450, SANTACHI650, VICON, NEON...
- Power: 12VDC-800mA, Communication Distance Max.2400m
- Baud Rate: 1200, 2400, 4800, 9600, 19200 bps.
- Size: 300(W) X 200(D) X 100(H)mm, -1.2Kg.
- Suitable for all cameras with RS-485 function

Megapixel HD Lenses



FIX IRIS Board mount (M12x0.5) Lenses

- **LVB-2460M** 1/3" HD IR Board Lens f=2.4~6mm/F1.6 HFOV: 1/3"=110°~45° • 1/4"=85°~33°
- **LVB-3580M** 1/3" HD IR Board Lens f=3.5~8mm/F1.6 HFOV: 1/3"=80°~34° • 1/4"=60°~26°
- **LB-021M** 1/3" HD IR Board Lens f=2.1mm/F2.0 HFOV: 1/3"=138° • 1/4"=100°
- **LB-028M** 1/3" HD IR Board Lens f=2.8mm/F1.8 HFOV: 1/3"=99° • 1/4"=78°
- **LB-036M** 1/3" HD IR Board Lens f=3.6mm/F1.8 HFOV: 1/3"=78° • 1/4"=58°
- **LB-06M** 1/3" HD IR Board Lens f=6.0mm/F1.8 HFOV: 1/3"=45° • 1/4"=33°
- **LB-08M** 1/3" HD IR Board Lens f=8.0mm/F1.8 HFOV: 1/3"=35° • 1/4"=25°
- **LB-12M** 1/3" HD IR Board Lens f=12mm/F1.8 HFOV: 1/3"=25° • 1/4"=17°
- **LB-16M** 1/3" HD IR Board Lens f=16mm/F1.8 HFOV: 1/3"=17° • 1/4"=12°

MANUAL IRIS CS mount Lens

- **LVB-2460M** 1/3" HD IR CS Lens f=2.4~6mm/F1.6 HFOV: 1/3"=110°~45° • 1/4"=85°~33°

FIX IRIS CS mount Lenses

- **LC-0155M** 1/2" HD IR CS Lens f=1.55mm/F2.0 HFOV: 1/3"=175° • 1/4"=130°
- **LC-036M** 1/3" HD IR CS Lens f=3.6mm/F1.8 HFOV: 1/3"=78° • 1/4"=58°
- **LC-06M** 1/3" HD IR CS Lens f=6.0mm/F1.8 HFOV: 1/3"=45° • 1/4"=33°
- **LC-08M** 1/3" HD IR CS Lens f=8.0mm/F1.8 HFOV: 1/3"=35° • 1/4"=25°
- **LB-12M** 1/3" HD IR CS Lens f=12mm/F1.8 HFOV: 1/3"=25° • 1/4"=17°
- **LB-16M** 1/3" HD IR CS Lens f=16mm/F1.8 HFOV: 1/3"=17° • 1/4"=12°



DV3.4x3.8SA-1

FUJINON 1/2" HD C-mount Lens
f=3.8~13mm/F1.4~ Close
Aspherical - Manual Iris - 3~5Mpix
HFOV (Horizontal angle of view)
1/2"=97°~28°
1/3"=71°~21°
1/4"=53°~15°



YV2.8x2.8SA-2

FUJINON 1/3" HD CS-mount Lens
f=2.8~8mm/F1.2~ Close
Aspherical - Manual Iris - 3~5Mpix
HFOV (Horizontal angle of view)
1/3"=99°~34°
1/4"=73°~26°



YV2.8x2.8SA-SA2-L

FUJINON 1/3" HD CS-mount Lens
f=2.8~8mm/F1.2~ Close
Auto Iris DC - Aspherical - 3~5Mpix
HFOV (Horizontal angle of view)
1/3"=99°~34°
1/4"=73°~26°



YV2.7x2.2SA-2

FUJINON 1/3" HD CS-mount Lens
f=2.2~6mm/F1.3~ Close
Aspherical - Manual Iris - 3~5Mpix
HFOV (Horizontal angle of view)
1/3"=120°~46°
1/4"=91°~34°